

NIC-300-USB



Benefits

- Full 802.11n support
- Supports passive 802.11ac site surveys
- Optimized for Ekahau products
- Quick and accurate site surveys
- Effective Wi-Fi troubleshooting
- USB interface
- Smooth RTLS deployment and analysis

Specifications

Supported Products

- Ekahau Site Survey
- Ekahau Tag Activator
- Ekahau Positioning Client

System Requirements

- Windows 7/Vista/XP/8
- USB interface

Antenna

- Integrated
- No external connector

Supported 802.11 Standards

- 802.11n (2.4 and 5GHz)
- 802.11b (2.4GHz)
- 802.11g (2.4GHz)
- 802.11a (5GHz)

Environment

- Operation: 0 to 55 Celsius
- Storage: 20 to 80 Celsius

Certifications

- FCC, CE

Wi-Fi Adapter for 802.11ac and 802.11n Site Surveys and RTLS Deployments

Ekahau NIC-300-USB Wi-Fi adapter is optimized for use with Ekahau products, such as Ekahau Site Survey and Ekahau RTLS. The NIC-300-USB is typically used by wireless network administrators as well as professional services engineers. It's perfect for accurately designing and troubleshooting wireless networks - and Wi-Fi based location tracking systems.

Ekahau NIC-300-USB fits into any laptop that has a USB interface - which is practically any laptop.

When used with Ekahau Site Survey, NIC-300-USB allows for quick and accurate site surveys on any 802.11ac as well as 802.11abgn network. Site surveys can be performed simultaneously for 2.4 and 5GHz frequency bands.

Ekahau NIC-300 is also optimized for deploying Ekahau Real-Time Location Tracking System (RTLS) on any 802.11 WLAN network using Ekahau Site Survey and Ekahau Activator*.

More Info

Website

ekahau.com/wifidesign

Order

E-mail: wifidesign@ekahau.com
Webshop: shop.ekahau.com

Support / Tech Questions

ekahau.com/support

Warranty

One year